

MODULOC Control Systems



LT2000-XT LASER DISTANCE METER FOR EXPLOSION PROOF APPLICATIONS



- **Visible Class II Laser providing precise distance measurement.**
- **Operates off Natural Surfaces up to 25 Meters (82 feet), off a white target at 85 Meters (279 Feet) and off a special reflector target at 125 Meters (410 Feet).**
- **Measuring rate as low as 100msec off of a white surface.**
- **Provides +/- 3mm to +/- 5mm accuracy.**
- **RS232 & RS422 Serial Interface**
- **Programmable 4-20 mA Analog Output**
- **External Trigger Input**
- **Cast Aluminum Housing Rated IP66, NEMA 4X Plus Explosion Proof Class I, Groups B, C, D, Class II, Groups E, F, G, Class III, NEMA 7BCD, NEMA 9EFG and ATEX IIC**

Typical Applications

Product Material	Length, width, thickness, level and position of product.
Material Handling	Automated Storage/Retrieval Systems and positioning of mobile equipment.
Crane Control	Positioning of cranes & crane trolleys.
Collision Avoidance	Distance alarm between vehicles using white target.

General Description

The LT2000-XT Laser Distance Meter operates over a substantial range off static or passing product in difficult areas in harsh hazardous and outdoor environments. The LT2000-XT measures distances over a working range up to 25 meters off of natural surfaces , up to 85 meters off of white surfaces and up to 125 meters off of a special reflector. For operation with automated positioning control of material handling transport systems a white reflective target is used or the special reflector is used.

Especially suited for precise detection and measurement of cold/hot product at temperatures up to 600°C.

Straightforward alignment is easily accomplished via the visible red laser measuring beam.

Accuracy is +/- 3mm to +/- 5mm according to ambient temperature and surface reflectivity. Repeatability is +/- 0.5mm and the user scalable resolution is 0.1mm.

The zero offset and the span of the 4 - 20 mA analog output are both user programmable. The distance offset is also user programmable, this allows the user to define a zero point independent of the analog output zero offset.

The LT2000-XT is provided with a user programmable digital switching output which is triggered by exceeding in the positive or negative direction a user programmable distance threshold. The hysteresis of the digital switching output is also programmable.

The LT2000-XT is a robust Laser Distance Meter and is provided in a Sand Cast Copper Free Aluminum Explosion Proof Housing. The Housing meets Explosion Proof Certifications for Class I, Groups B, C, D; Class II, Groups E, F, G; Class III, NEMA 7BCD, NEMA 9EFG and ATEX IIC. The Housing can also be used in IP66 and NEMA 4X Water Tight Applications. The Housing has a corrosion Resistant, "Safety Blue" Polyester Powder Coating and utilizes Stainless Steel Hardware. Standard operating temperature is 50°C.

The LT2000-XT laser distance meter provides a highly accurate measurement reading. It is ideal for length, width, thickness, depth, height, position determination.

The LT2000-XT is supplied a standard with either a RS232 or RS422/RS485 serial interface with a 2400 to 38,400 Baud Rate & a programmable 4 - 20 mA 16 BIT analog output. An optional ProfiBus DP Gateway Interface Box is available. ProfiBus DP, DeviceNet, and Ethernet Interface Options will soon be available.

MODULOC Technology - The Total Laser Solution

MODULOC Control Systems Ltd.

Wheathamstead, Hertfordshire, AL4 8SB United Kingdom
Phone: +44 (0)845 8736501 FAX: +44 (0)1582 831980
E-Mail: sales@moduloc-intl.com Website: www.moduloc-intl.com

MODULOC Control Systems, Inc.

500 Garden City Drive. - Suite 2B, Monroeville, PA 15146 USA
Phone: 412-824-1260 FAX: 412-824-8890
E-Mail: sales@moduloc-usa.com Website: www.moduloc-usa.com

